

Intended Use

Ideal for applications requiring attractive, quick-installation exit signs and low energy consumption.

Construction

Precision-molded thermoplastic housing is impact- and scratch-resistant, corrosion-proof and UV-stabilized to resist discoloration.

Innovative snap-together design allows installation in less than three minutes.

Long-life LEDs feature very low energy consumption and rated life up to 10 years. Consumes less than one watt of energy.

Fully assembled single-face exit with optional extra faceplate for easy field conversion to double-face standard.

Replaceable chevron directional indicator knockouts for choice of direction.

Universal (top, end or back) mounting with canopy included.

Automatic recharge after discharge.

Conveniently located test switch and status indicator provide visual and manual means of monitoring system operation.

The self-diagnostic emergency signs comply with NFPA Life Safety Code® and automatically test the battery once a month for five minutes and once every six months for 30 minutes.

U.S. Patent No. 5, 526, 251; 5, 611, 163; 5, 739, 639 and 5, 954, 423. Other patents pending.

Listings

UL Listed. Meets UL924. UL damp location listing 50° to 104°F (10°C to 40°C) standard. NOM Certified (see Options).

LQM
Quantum® Thermoplastic



ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: LQM S W 3 R 120/277 EL N

Series	Face type	Housing	Number of faces	Letter color	Voltage	Options
LQM LED	S Stencil	(blank) Black W White	3 Single with extra faceplate and color panel for field conversion to double-face	R Red G Green	120/277 Dual voltage ¹	(blank) Standard non-emergency EL N Nickel-cadmium battery SD Self diagnostics ² X2 Lamps wired on two separate circuits ³ NOM Meets Mexican standards ⁴

ADDITIONAL INFORMATION

For additional product information, visit www.lithonia.com.

ELECTRICAL APPLICATION DATA

TYPE	VOLTS	AMPS	WATTS
Standard LED Red	120	.05	.62
Standard LED Red	277	.06	.69
Standard LED Green	120	.05	.62
Standard LED Green	277	.06	.74
Emergency LED Red	120	.05	.71
Emergency LED Red	277	.06	.92
Emergency LED Green	120	.05	.66
Emergency LED Green	277	.06	.70




ACCESSORIES

ORDER SEPARATELY

ELA W US12	12" stem kit with white canopy ⁵
ELA WG1	Back-mount wireguard
ELA WGEXT	Top-mount wireguard
ELA WGEXE	End-mount wireguard

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.

Shipping weight 2.6 lbs (1.2 kg)



Notes

- 1 Some special voltages available. Consult factory.
- 2 Available with EL N operation only.
- 3 Available with AC operation only.
- 4 Available with stencil or panel faces in white housing and red letters only.
- 5 Replace W with B for black canopy.