




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L2				1492-L2T				1492-L2Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block with 2 connection points per side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC
Maximum Current	15 A	20 A	17.5 A	15 A	20 A	17.5 A	15 A	15 A	20 A	17.5 A	15 A	15 A
Wire Range (Rated Cross Section)	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.			
Color	Grey		1492-L2	50	1492-L2T		50	1492-L2Q		50		
	Red		1492-L2-RE	50	1492-L2T-RE		50	1492-L2Q-RE		50		
	Blue		1492-L2-B	50	1492-L2T-B		50	1492-L2Q-B		50		
	Black		1492-L2-BL	50	1492-L2T-BL		50	1492-L2Q-BL		50		
	Green		1492-L2-G	50	1492-L2T-G		50	1492-L2Q-G		50		
	Yellow		1492-L2-Y	50	1492-L2T-Y		50	1492-L2Q-Y		50		
	Orange		1492-L2-OR	50	1492-L2T-OR		50	1492-L2Q-OR		50		
	Brown		1492-L2-BR	50	1492-L2T-BR		50	—		—		
	White		1492-L2-W	50	1492-L2T-W		50	1492-L2Q-W		50		
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.			
Mounting Rails 1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10	199-DR1		10			
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10	1492-DR5		10			
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2	1492-DR6		2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2	1492-DR7		2			
End Barriers	Grey		1492-EBL2	50	1492-EBL2T		50	1492-EBL2Q		50		
	Blue		1492-EBL2-B	50	1492-EBL2T-B		50	1492-EBL2Q-B		50		
	Yellow		1492-EBL2-Y	50	1492-EBL2T-Y		50	1492-EBL2Q-Y		50		
End Anchors and Retainers Screwless End Retainer	1492-ERL35		20	1492-ERL35		20	1492-ERL35		20			
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100			
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50			
Jumpers Plug-in Center Jumper — 10-Pole	1492-CJL4-10		20	1492-CJL4-10		20	1492-CJL4-10		20			
Plug-in Center Jumper — 5-Pole	1492-CJL4-5		60	1492-CJL4-5		60	1492-CJL4-5		60			
Plug-in Center Jumper — 4-Pole	1492-CJL4-4		60	1492-CJL4-4		60	1492-CJL4-4		60			
Plug-in Center Jumper — 3-Pole	1492-CJL4-3		60	1492-CJL4-3		60	1492-CJL4-3		60			
Plug-in Center Jumper — 2-Pole	1492-CJL4-2		60	1492-CJL4-2		60	1492-CJL4-2		60			
Other Accessories Reducing Sleeves #28...#24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2		100	1492-PSL2-2		100	1492-PSL2-2		100			
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-PSL2-5		100	1492-PSL2-5		100	1492-PSL2-5		100			
Test Plug (Stackable)	1492-TPL4		25	1492-TPL4		25	1492-TPL4		25			
Electrical Warning Plate	1492-EWPL4		20	1492-EWPL4		20	1492-EWPL4		20			
Marking Systems Snap-In Marker Cards	1492-M3X12 (120/card)		5	1492-M3X12 (120/card)		5	1492-M3X12 (120/card)		5			
Snap-In Marker Cards	1492-M3X5 (100/card)		5	1492-M3X5 (100/card)		5	1492-M3X5 (100/card)		5			

	1492-L3				1492-L3T				1492-L3Q			
--	---------	--	--	--	----------	--	--	--	----------	--	--	--

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	<i>Feed-through terminal block</i>				<i>Feed-through terminal block with 3 connection points, 2 on one side</i>				<i>Feed-through terminal block with 2 points on each side</i>			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A
Wire Range (Rated Cross Section)	#30...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating (SCCR)	See Short-Circuit Current Ratings — Fuse Ratings											

Terminal Blocks		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color	Grey	1492-L3	100	1492-L3T	100	1492-L3Q	100
	Red	1492-L3-RE	100	1492-L3T-RE	100	1492-L3Q-RE	100
	Blue	1492-L3-B	100	1492-L3T-B	100	1492-L3Q-B	100
	Black	1492-L3-BL	100	1492-L3T-BL	100	1492-L3Q-BL	100
	Green	1492-L3-G	100	1492-L3T-G	100	1492-L3Q-G	100
	Yellow	1492-L3-Y	100	1492-L3T-Y	100	1492-L3Q-Y	100
	Orange	1492-L3-OR	100	1492-L3T-OR	100	1492-L3Q-OR	100
	Brown	1492-L3-BR	100	1492-L3T-BR	100	1492-L3Q-BR	100
	White	1492-L3-W	100	1492-L3T-W	100	1492-L3Q-W	100

Accessories		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails	1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10
	1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10
	1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2
	1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2
End Barriers	Grey	1492-EBL3	50	1492-EBL3T	50	1492-EBL3Q	50
	Blue	1492-EBL3-B	50	1492-EBL3T-B	50	1492-EBL3Q-B	50
	Yellow	1492-EBL3-Y	50	1492-EBL3T-Y	50	1492-EBL3Q-Y	50
End Anchors and Retainers	Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20
	DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100
	DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50
Jumpers	Plug-in Center Jumper — 50-Pole	1492-CJK5-50	10	1492-CJK5-50	10	1492-CJK5-50	10
	Plug-in Center Jumper — 10-Pole	1492-CJK5-10	20	1492-CJK5-10	20	1492-CJK5-10	20
	Plug-in Center Jumper — 9-Pole	1492-CJK5-9	20	1492-CJK5-9	20	1492-CJK5-9	20
	Plug-in Center Jumper — 8-Pole	1492-CJK5-8	20	1492-CJK5-8	20	1492-CJK5-8	20
	Plug-in Center Jumper — 7-Pole	1492-CJK5-7	20	1492-CJK5-7	20	1492-CJK5-7	20
	Plug-in Center Jumper — 6-Pole	1492-CJK5-6	20	1492-CJK5-6	20	1492-CJK5-6	20
	Plug-in Center Jumper — 5-Pole	1492-CJK5-5	20	1492-CJK5-5	20	1492-CJK5-5	20
	Plug-in Center Jumper — 4-Pole	1492-CJK5-4	60	1492-CJK5-4	60	1492-CJK5-4	60
	Plug-in Center Jumper — 3-Pole	1492-CJK5-3	60	1492-CJK5-3	60	1492-CJK5-3	60
	Plug-in Center Jumper — 2-Pole	1492-CJK5-2	60	1492-CJK5-2	60	1492-CJK5-2	60
Other Accessories	Reducing Sleeves #30...#24 AWG (0.13...0.2 mm ²) White	1492-PSL3-2	100	1492-PSL3-2	100	1492-PSL3-2	100
	Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-PSL3-5	100	1492-PSL3-5	100	1492-PSL3-5	100
	Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL3-10	100	1492-PSL3-10	100	1492-PSL3-10	100
	Test Plug	1492-TP23	20	1492-TP23	20	1492-TP23	20
	Test Plug (Stackable)	1492-TPL5	25	1492-TPL5	25	1492-TPL5	25
	Electrical Warning Plate	1492-EWPL5	20	1492-EWPL5	20	1492-EWPL5	20
Marking Systems	Snap-In Marker Cards	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5







Snap-In Marker Cards	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5
Hinged Marker Cards	1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)	5
Hinged Marker Cards	1492-MH5X15 (96/card)	5	1492-MH5X15 (96/card)	5	1492-MH5X15 (96/card)	5

		1492-L4				1492-L4T				1492-L4Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.													
Specifications		Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 connection points on each side			
Certifications			CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating		600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current		33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A
Wire Range (Rated Cross Section)		#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)
Wire Strip Length		0.47 in. (12 mm)				0.47 in. (12 mm)				0.47 in. (12 mm)			
Density		49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range		-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating		See Short-Circuit Current Ratings — Fuse Ratings											
Terminal Blocks		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.			
Color	Grey	1492-L4		50	1492-L4T		50	1492-L4Q		50			
	Red	1492-L4-RE		50	—		—	1492-L4Q-RE		50			
	Blue	1492-L4-B		50	1492-L4T-B		50	1492-L4Q-B		50			
	Black	1492-L4-BL		50	1492-L4T-BL		50	1492-L4Q-BL		50			
	Green	1492-L4-G		50	1492-L4T-G		50	1492-L4Q-G		50			
	Yellow	1492-L4-Y		50	1492-L4T-Y		50	1492-L4Q-Y		50			
	Orange	1492-L4-OR		50	1492-L4T-OR		50	1492-L4Q-OR		50			
	Brown	1492-L4-BR		50	1492-L4T-BR		50	1492-L4Q-BR		50			
	White	1492-L4-W		50	1492-L4T-W		50	1492-L4Q-W		50			
Accessories		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.			
Mounting Rails		199-DR1		10	199-DR1		10	199-DR1		10			
1 m Symmetrical DIN (Steel)		1492-DR5		10	1492-DR5		10	1492-DR5		10			
1 m Symmetrical DIN (Aluminum)		1492-DR6		2	1492-DR6		2	1492-DR6		2			
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR7		2	1492-DR7		2	1492-DR7		2			
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-ERL35		20	1492-ERL35		20	1492-ERL35		20			
End Barriers		1492-EBL4		50	1492-EBL4T		50	1492-EBL4Q		50			
	Grey	1492-EBL4-B		50	1492-EBL4T-B		50	1492-EBL4Q-B		50			
	Blue	1492-EBL4-Y		50	1492-EBL4T-Y		50	1492-EBL4Q-Y		50			
	Yellow	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100			
End Anchors and Retainers		1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100			
Screwless End Retainer		1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50			
DIN Rail — Normal Duty		1492-CJK6-10		20	1492-CJK6-10		20	1492-CJK6-10		20			
DIN Rail — Heavy Duty		1492-CJK6-9		20	1492-CJK6-9		20	1492-CJK6-9		20			
Jumpers:		1492-CJK6-8		20	1492-CJK6-8		20	1492-CJK6-8		20			
Plug-in Center Jumper — 10-Pole		1492-CJK6-7		20	1492-CJK6-7		20	1492-CJK6-7		20			
Plug-in Center Jumper — 9-Pole		1492-CJK6-6		20	1492-CJK6-6		20	1492-CJK6-6		20			
Plug-in Center Jumper — 8-Pole		1492-CJK6-5		20	1492-CJK6-5		20	1492-CJK6-5		20			
Plug-in Center Jumper — 7-Pole		1492-CJK6-4		60	1492-CJK6-4		60	1492-CJK6-4		60			
Plug-in Center Jumper — 6-Pole		1492-CJK6-3		60	1492-CJK6-3		60	1492-CJK6-3		60			
Plug-in Center Jumper — 5-Pole		1492-CJK6-2		60	1492-CJK6-2		60	1492-CJK6-2		60			
Plug-in Center Jumper — 4-Pole		1492-PSL4-2		100	1492-PSL4-2		100	1492-PSL4-2		100			
Plug-in Center Jumper — 3-Pole		1492-PSL4-2		100	1492-PSL4-2		100	1492-PSL4-2		100			
Plug-in Center Jumper — 2-Pole		1492-PSL4-2		100	1492-PSL4-2		100	1492-PSL4-2		100			
Other Accessories		1492-PSL4-2		100	1492-PSL4-2		100	1492-PSL4-2		100			
Reducing Sleeves #26...#24 AWG (0.13...0.2 mm ²) White		1492-PSL4-2		100	1492-PSL4-2		100	1492-PSL4-2		100			

Reducing Sleeves #20...#22 AWG (0.25...0.5 mm ²) Grey	1492-PSL4-5	100	1492-PSL4-5	100	1492-PSL4-5	100
Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL4-10	100	1492-PSL4-10	100	1492-PSL4-10	100
Test Plug	1492-TP23	20	1492-TP23	20	1492-TP23	20
Test Plug (Stackable)	1492-TPL6	25	1492-TPL6	25	1492-TPL6	25
Electrical Warning Plate	1492-EWPL6	20	1492-EWPL6	20	1492-EWPL6	20
Marking Systems Snap-In Marker Cards	1492-M6X10 (120/card)	5	1492-M6X10 (120/card)	5	1492-M6X10 (120/card)	5
Snap-In Marker Cards	1492-M6X5 (200/card)	5	1492-M6X5 (200/card)	5	1492-M6X5 (200/card)	5
Hinged Marker Cards	1492-MH6X12 (80/card)	5	1492-MH6X12 (80/card)	5	1492-MH6X12 (80/card)	5

	1492-L6				1492-L6T				1492-L10			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC	
Maximum Current	50 A		41 A	36 A	50 A		41 A	36 A	60 A	55 A	57 A	50 A
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	#16...6 AWG	10 mm ²	10 mm ² (16...8 AWG)	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)			
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft (123 pcs/m)				30 pcs/ft (99 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See Short-Circuit Current Ratings — Fuse Ratings											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color	Grey	1492-L6	50	1492-L6T	50	1492-L10	25	Red	1492-L6-RE	50	1492-L10-RE	25
	Blue	1492-L6-B	50	1492-L6T-B	50	1492-L10-B	25	Black	1492-L6-BL	50	1492-L10-BL	25
	Green	1492-L6-G	50	1492-L6T-G	50	1492-L10-G	25	Yellow	1492-L6-Y	50	1492-L10-Y	25
	Orange	1492-L6-OR	50	1492-L6T-OR	50	1492-L10-OR	25	Brown	1492-L6-BR	50	1492-L10-BR	25
	White	1492-L6-W	50	1492-L6T-W	50	1492-L10-W	25					
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails 1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barriers	Grey	1492-EBL6	50	1492-EBL6T	50	1492-EBL10	20	Blue	—	50	1492-EBL10-B	20
	Yellow	1492-EBL6-Y	50	1492-EBL6T-Y	50	1492-EBL10-Y	20					
End Anchors and Retainers Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Jumpers Plug-in Center Jumper — 32-Pole	1492-CJL8-32		10		1492-CJL8-32		10		—		—	
Plug-in Center Jumper — 4-Pole	1492-CJL8-4		60		1492-CJL8-4		60		—		—	
Plug-in Center Jumper — 3-Pole	1492-CJL8-3		60		1492-CJL8-3		60		—		—	
Plug-in Center Jumper — 2-Pole	1492-CJL8-2		60		1492-CJL8-2		60		1492-CJL10-2		25	
Other Accessories Test Plug	—		—		—		—		1492-TP23		20	
Test Plug (Stackable)	1492-TPL8		25		1492-TPL8		25		—		—	
Electrical Warning Plate	1492-EWPL8		20		1492-EWPL8		20		1492-EWPL10		20	
Marking Systems Snap-In Marker Cards*	1492-M6X12 (120/card)		5		1492-M6X12 (120/card)		5		1492-M6X12 (120/card)		5	
Snap-In Marker Cards	1492-MR8X12 (84/card)		5		1492-M8X5 (160/card)		5		1492-M8X5 (160/card)		5	
Hinged Marker Cards	1492-MH6X12 (80/card)		5		1492-MH6X12 (80/card)		5		1492-MH5X15 (96/card)		5	

* May only be mounted in terminal block corner marking positions.

	1492-L16			1492-L16D*			1492-L35					
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block			Power distribution block with center jumper connection/feed			Feed-through terminal block					
Certifications		CSA	IEC	ATEX		CSA	IEC		CSA	IEC	ATEX	
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		500V AC/DC	600V AC/DC	800V AC/DC	690V AC/DC		
Maximum Current	65 A		76 A	66 A	65 A		76 A	120 A	125 A	109 A		
Wire Range (Rated Cross Section)	#14...4 AWG		16 mm ²	16 mm ² (16...6 AWG)	#14...4 AWG		16 mm ²	#12...2 AWG	35 mm ²	35 mm ² 14...2 AWG		
Wire Strip Length	0.70 in. (18 mm)			0.70 in. (18 mm)			0.98 in. (25 mm)					
Density	25 pcs/ft (82 pcs/m)			20 pcs/ft (66 pcs/m)			18 pcs/ft (62 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating	See Short-Circuit Current Ratings — Fuse Ratings											
Terminal Blocks	Cat. No.			Pkg Qty.			Cat. No.			Pkg Qty.		
Color	Grey	1492-L16		25	1492-L16D*	20		1492-L35	10			
	Red	1492-L16-RE		25	—	—		1492-L35-RE	10			
	Blue	1492-L16-B		25	—	—		1492-L35-B	10			
	Black	1492-L16-BL		25	—	—		1492-L35-BL	10			
	Green	1492-L16-G		25	—	—		1492-L35-G	10			
	Yellow	1492-L16-Y		25	—	—		1492-L35-Y	10			
	Orange	1492-L16-OR		25	—	—		1492-L35-OR	10			
	Brown	1492-L16-BR		25	—	—		1492-L35-BR	10			
	White	1492-L16-W		25	—	—		1492-L35-W	10			
Accessories	Cat. No.			Pkg Qty.			Cat. No.			Pkg Qty.		
Mounting Rails 1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1	10		199-DR1	10				
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)	199-DR4		5	199-DR4	5		199-DR4	5				
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5	10		1492-DR5	10				
1 m HI-Rise Symmetrical DIN (Aluminum)	1492-DR6		2	1492-DR6	2		1492-DR6	2				
1 m Angled HI-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7	2		1492-DR7	2				
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8		5	1492-DR8	5		1492-DR8	5				
1 m Symmetrical Heavy Duty DIN (Steel Slotted)	1492-DR9		5	1492-DR9	5		1492-DR9	5				
End Barriers	Grey	1492-EBL16		20	Integrated to Block	—		Integrated to Block	—			
	Blue	1492-EBL16-B		20	—	—		—	—			
	Yellow	1492-EBL16-Y		20	—	—		—	—			
End Anchors and Retainers Screwless End Retainer	1492-ERL35		20	1492-ERL35	20		1492-ERL35	20				
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35	100		1492-EAJ35	100				
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35	50		1492-EAHJ35	50				
Jumpers Plug-in Center Jumper — 2-Pole	1492-CJL12-2		25	‡	—		1492-CJL16-2	10				
Other Accessories Test Plug	1492-TP23		20	1492-TP23	20		1492-TP23	20				
Test Adapter	—		—	—	—		—	—				
Electrical Warning Plate	1492-EWPL12		20	1492-EWPL12	20		1492-EWPL16	20				
Marking Systems Snap-In Marker Cards§	1492-M7X12 (108/card)		5	1492-M7X12 (108/card)	5		1492-M7X12 (108/card)	5				
Snap-In Marker Cards	1492-M8X5 (160/card)		5	1492-M8X5 (160/card)	5		1492-M8X5 (160/card)	5				
Hinged Marker Cards	1492-MH5X15 (96/card)		5	1492-MH5X15 (96/card)	5		1492-MH5X15 (96/card)	5				

* Can be electrically connected through center jumper for power distribution to 1492 - L3, L3Q, L4, L4T, L4Q, L6, and L6T terminal blocks. See **Feed Left** for distribution guidelines.

‡ Use defined center jumper for standard terminal blocks when connecting for power distribution.

§ May only be mounted in terminal block corner marking positions.

