


HBL2331 -- Twist-Lock Plug



2P3W, 20A 277V AC, L7-20P, Black & White Nylon

Product Specifications

<p>Product Type</p>	 <p style="text-align: center;">Twist-Lock Devices</p>
<p>Product Item</p>	<p>Plug</p>
<p>Wiring Scheme</p>	<p>2 Pole, 3 Wire Grounding</p>
<p>Amperage</p>	<p>20A</p>
<p>Voltage</p>	<p>277V AC</p>
<p>NEMA Configuration</p>	<p>L7-20P</p>
<p>Item Style</p>	<p>Insulgrip</p>
<p>Device Color</p>	<p>Black/White</p>
<p>Horsepower</p>	<p>2</p>
<p>Cord Dia.</p>	<p>.360"-.930" (9-24)</p>
<p>Blade Holder Material</p>	<p>Natural White Nylon</p>
<p>Terminal Retainer Material</p>	<p>Clear polycarbonate</p>
<p>Housing Material</p>	<p>Black nylon</p>
<p>Cord Clamp Material</p>	<p>Natural (white) nylon</p>

Blade Material	Brass
Terminal Clamp Material	.08" (2) steel-nickel plated
Terminal Screw Material	#10-32 Brass (white finish on neutral screw when used) Multi-drive
Ground Screw Material	#10-32 Brass (green finish) Multi-drive
Cord Clamp Screw Material	Steel, zinc plated Multi-drive
Body Holding Screw Material	Steel, zinc plated Multi-drive
Ratings	Molded into face
Catalog No.	Permanently ink marked on body.
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30 C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	20A #12 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	FED SPEC UL/CSA
Feature Info	Black and white nylon.
UPC Number	78358503789
Weight in LBs	0.3

