

## Cold Shrink QT-III Outdoor Skirted Termination

Kit Number	BIL	Cable Insulation	Conductor Size Range					UPC (054007-)
		O.D. Range in. (mm)	5 kV	8.7 kV	15 kV	25/28 kV	35 kV	
<b>Shielded Cable Kits</b> (Each kit makes three terminations)								
7620-S-2	95 kV	0.32 – 0.59 (8,2 – 15,0)	8 – 4	8 – 6	—	—	—	42168
7621-S-2	95 kV	0.44 – 0.89 (11,2 – 22,7)	2 – 3/0	4 – 2/0	—	—	—	42169
7622-S-2	110 kV	0.64 – 1,08 (16,3 – 27,4)	4/0 – 400	3/0 – 300	2 – 4/0 (35 – 120)	—	—	42170
7692-S-4	150 kV	0.64 – 1,08 (16,3 – 27,4)	4/0 – 400	3/0 – 300	2 – 4/0 (35 – 120)	2 – 1/0 (35 – 50)	—	42211
7693-S-4	150 kV	0.72 – 1.29 (18,3 – 32,8)	300 – 500	250 – 500	2/0 – 300 (70 – 150)	2 – 4/0 (35 – 120)	—	42212
7694-S-4	150 kV	0.83 – 1.53 (21,1 – 38,9)	500 – 750	350 – 700	4/0 – 500 (120 – 240)	2/0 – 250 (70 – 150)	—	42213
7695-S-4	150 kV	1.05 – 1.80 (26,7 – 45,7)	700 – 1500	600 – 1250	500 – 1000 (240 – 500)	250 – 800 (125 – 400)	—	42214
7696-S-4	150 kV	1.53 – 2.32 (38,9 – 58,9)	1750 – 2000	1500 – 2000	1250 – 2000 (625 – 1000)	900 – 1750 (500 – 800)	—	42215
7683-S-8	200 kV	0.72 – 1.29 (18,3 – 32,8)	300 – 500	250 – 500	2/0 – 300 (70 – 150)	2 – 4/0 (35 – 120)	2 – 2/0 (35 – 70)	42465
7684-S-8	200 kV	0.83 – 1.53 (21,1 – 38,9)	500 – 750	350 – 700	4/0 – 500 (120 – 240)	2/0 – 250 (70 – 150)	2 – 4/0 (35 – 120)	42466
7685-S-8	200 kV	1.05 – 1.80 (26,7 – 45,7)	700 – 1500	600 – 1250	500 – 1000 (240 – 500)	250 – 800 (125 – 400)	3/0 – 600 (95 – 325)	42467
7686-S-8	200 kV	1.53 – 2.32 (38,9 – 58,9)	1750 – 2000	1500 – 2000	1250 – 2000 (625 – 1000)	900 – 1750 (500 – 800)	700 – 1500 (400 – 725)	42468