



DIE, COND, SPEED, SS 1-7/32" (30.5MM)

"Die, 1-7/32"" (30.5) Dia., SPEED PUNCH??? System for Stainless Steel."

Cat No: 52066010

UPC No: 783310016687

Description

- SPEED PUNCH® saves time and money with every hole.
- Up to 3X's faster setup and disassembly.
- No-Thread punch design eliminates cross-threading.
- Available for
 - Stainless Steel - 1/2" to 2" conduit size
 - Mild Steel - 1/2" to 4" conduit size
 - Metric ISO-16 to ISO-63
 - 22mm & 30mm for Oil tight push buttons.

Specifications

- Application : For punching holes in stainless steel, mild steel, aluminum, fiberglass, and plastic
- Capacity Mild Steel : Max: 10 gauge (3.0 mm).
- Capacity Stainless Steel : Max: 10 gauge (3.0 mm).
- Diameter : Actual hole size: 1.210" (30.5 MM)
- Draw Stud : Std. Draw Stud: 7212SP23 (3/4" X 5.00")
- Draw Studs : Alt. Draw Stud (Long): 7212SP21 (3/4" x 5.83") - For use with 746 Hydraulic Ram
- Driver : Use with Greenlee Punch Drivers: 746 Hydraulic Ram & 767 Pump (or LS50L - Battery-Powered Driver up to max. 12 ga. stainless steel).
- Material : Carbon-Alloy Steel, Zinc Plated
- Minimum Pilot Hole : 7/8" (22.2 mm)
- Operation : Must be used with other SPEED PUNCH® System components.
- Sub Brand : SPEED PUNCH®#174
- Type : Knockout Punches
- Weight : 0.75 lbs. (0.34 kg)