



BURNDY Catalog Number	K11A30U
UPC Number	781810370261
Description	TWO:6 STR-300 DUAL RATED
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	1
Length (in)	3
Height (in)	2.03
Thickness	0.5
D - in	0.94
Stud Size (Fraction)	5/16
N (in)	0.47
General	
Number of Conductors	2
Number of Holes	2
Product Description	Aluminum Universal Terminal, 1 Hole, Two: 6 AWG (Str)-300 kcmil, 5/16" Stud, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	6 AWG-300 kcmil
Copper Solid Size (Range)	4 AWG-4/0 AWG
Copper Stranded (Range)	6 AWG-300 kcmil
Physical	
Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175

