

EZGround™ Compression Grounding Connectors

One-piece construction for cable-to-cable, cable-to-rod, “T” and “X” connections.

Cable-to-Cable or Cable-to-Rod Connectors

- Suitable for direct burial or in concrete
- Replaces exothermic welds
- Made from high-conductivity wrought copper
- Conforms to IEEE 837 standard
- UL® 467



DB

CAT. NO.	CABLE TO CABLE RANGE				GROUND ROD	ROD TO CABLE		
	MAIN	DIE CODE	BRANCH	DIE CODE		DIE CODE	CABLE	DIE CODE
GG21-21	#2 or #1	45	#2 or #1	45	—	—	—	—
GG10-10	1/0	54	1/0	54	—	—	—	—
GG2030-21	2/0 or 3/0	60	#2	45	—	—	—	—
GG2030-10	2/0 or 3/0	60	1/0	54	—	—	—	—
GG2030-2030	2/0 or 3/0	60	2/0 or 3/0	50	—	—	—	—
GG40250-21	4/0 or 250	71	#2	45	1/2"	71	#2 or #1	45
			#1	50	3/8"	80H	#2 or #1	50
GG40250-10	4/0 or 250	71	1/0	54	1/2"	71	1/0	65
					3/8"	80H		
GG40250-2030	4/0 or 250	71	2/0 or 3/0	60	1/2"	71	2/0 or 3/0	60
					3/8"	80H	2/0 or 3/0	60
GG40250-40250	4/0 or 250	71	4/0 or 250	71	1/2"	71	4/0 or 250	71
					3/8"	80H	4/0 or 250	71
GG350-350	350 kcmil	80H	350	80H	—	—	—	—
GG500-40250	500 kcmil	87	4/0 or 250	71	3/8"	80H	500	87
					1/4"	87H	500	87
GG500-500	500 kcmil	87	500	87	3/4"	87	500	87
GG500-350	500 kcmil	87H	350	80	3/8"	87H	350	80H
					1/4"			
GG500-2030	500 kcmil	87H	2/0 or 3/0	60	3/8"	87H	2/0 or 3/0	60
					1/4"			