



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Ferrule style high speed fuse links

**FWP-50A14FI**

**UPC:**051712542814

### Dimensions:

- **Height:** 32 MM
- **Length:** 52 MM
- **Width:** 15 MM

**Weight:**.012 KG

**Notes:**Low arc voltage, excellent cycling capability and DC performance

### Warranties:

- Not Applicable

### Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 50A
- **Voltage Rating:** 690 Vac
- **Interrupt Rating:** 200kA ac RMS Symmetrical, 50kA at 300 Vdc
- **Fuse Indicator:** With Indicator
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I<sup>2</sup>T):** 200
- **Clearing (I<sup>2</sup>T):** Clearing at Rated voltage: 1800
- **Diameter:** 14 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 9.8W



- **Mounting:** Fuse holder and blocks
- **Quantity:** 10
- **Fuse Size:** 14 x 51 mm

**Supporting documents:** No Data

**Certifications:**

- CSA Certified
- UL Recognized

**Product compliance:**

- CE Marked