

# Mercmaster™ III Low Profile Compact Fluorescent Luminaires

## Enclosed and Gasketed. For Hazardous and Wet Locations

Compact Fluorescent listed for simultaneous exposure to combustible dusts and flammable gases or vapors.

*Class I, Division 2, Groups A, B, C, D  
Class I, Zone 2, AEx nA nR IIC (Z2)  
Class I, Zone 2, Ex nR IIC (Z) vA*

*Class II, Division 1 and 2, Groups E, F, G  
Class III  
Simultaneous Exposure (Class I, Division 2/  
Class II, Division 1)*

*Fixtures Outside Type (Salt Water)  
Type 4X  
IP66*

### Applications

- Enclosed and gasketed fixtures suitable for use in marine and wet locations, and in a wide range of industrial, chemical processing and other areas where flammable gases and vapors or combustible dusts are present under conditions defined by the National Electrical Code as Class I, Division 2; Class II, Division 1 and 2; and Class III. The method of protection for the Zone 2 Mercmaster is AEx nA nR – Restricted Breathing/ Nonsparking.
- For use in areas of low clearance, low ceiling heights or where fixture weights must be minimized.
- Suited for use in non-hazardous locations where severe weather conditions, excessive moisture, dirt, dust or corrosive atmospheres are present.
- Typical applications include oil refineries, pulp and paper mills, chemical plants, food-processing areas, inspection facilities, foundries, power plants, storage areas, waste and sewage treatment, parking garages, and other areas where dust, water, dirt and rough usage are a problem.

### Features

- Energy-efficient, compact fluorescent light sources possess superior lamp efficiency.
- Fluorescent provides long lamp life, thereby reducing relamping costs.
- "Instant on" nature of this electronically ballasted fluorescent eliminates the possibility of an extended blackout due to a momentary power dip.
- High efficacies (up to 75 lumens per Watt) offer a desirable low-glare/instant-on alternative to low wattage HID sources.
- High output under widely varying conditions: Greater than 90% of rated lumens in ambient temperatures from 23 °F to 130 °F / -5 °C to 54 °C.
- Excellent color rendering (82 CRI) makes it the best choice for food processing and inspection facilities.
- A wide variety of lamp wattages: 26 W, 32 W, 42 W, 52 W, 64 W, 84 W.
- Electronic ballast permits low operating costs with power factor greater than 99%. Also allows flicker-free starting.
- Cold weather starting to a minimum temperature of 0°F/ -18°C.
- Fixtures are available for operation from an external 125 Vdc source.
- Compact, light-weight low profile design creates ease of installation and maintenance.
- Modular design, with multiple mounting hoods, optics and reflectors, permits a wide array of fixtures to meet installation and lighting needs.
- Body gaskets and optic gaskets are high temperature silicone O-Rings that provide superior sealing.
- Mounting hoods have a high hinge for added safety during installation and servicing.
- Choice of heat-resistant prismatic glass refractor (NEMA I, III or V), heat-resistant clear globes, color globes or polymeric refractors (NEMA II, III, IV or V). (Polymeric refractors are not listed for Zone 2.)



Pendant Mount Fixture  
with Glass Globe



Ceiling Mount Fixture with  
Prismatic Glass Refractor

### Standard Materials

- Standard dome or 30° angle reflectors: highly reflective fiberglass reinforced white polyester to provide strength, corrosion resistance and excellent photometrics
- Fixture housing, mounting hoods, and guards: die-cast, copperfree (4/10 of 1% max.) aluminum with epoxy finish for corrosion resistance
- Exposed hardware: stainless steel. Latch assemblies have stainless steel bolt and captive nut; reflectors and guards attach with stainless steel screws threading into stainless steel inserts
- Globes and glass refractors: heat-resistant prismatic glass
- Polymeric refractor: spun aluminum reflector and a lens made of an engineered thermoplastic

### Standard Finishes

- Epoxy powder coat finish electrostatically applied for complete, uniform surface protection

### Options

- Fuse can be field installed. Kits include fuse block, wire connectors and screws for attachment to mounting hood.
  - Fixtures with fuses do not comply with UL 1598A for marine listing
  - Canadian Electrical Code does NOT allow fusing in hazardous locations vA
- Guards with gray epoxy painted to match fixtures, supplied with stainless steel screws. Add suffix **-G**.
- Reflectors are available as standard dome and 30° angle polyester. Order separately.

### Certifications and Compliances

- UL Standard: UL 1598, UL 1598A, UL 844, UL 60079-0, UL 60079-15
- UL Listed: E10444
- CSA Standard: C22.2 No. 250, C22.2 No. 137, CAN E60079-0, CAN E60079-15
- CSA Certified: 025428


vA CSA Certification Only.

# Mercmaster™ III Low Profile Compact Fluorescent Luminaire Family Tree

Enclosed and Gasketed. For Hazardous and Wet Locations

Compact Fluorescent listed for simultaneous exposure to combustible dusts and flammable gases or vapors.

## Mounting Hoods











LIGHTING: ENCLOSED AND GASKETED - AREA - FLUORESCENT

<sup>CSA</sup> CSA Certification Only.

# Mercmaster™ III Low Profile Compact Fluorescent Luminaire Accessories

## Enclosed and Gasketed. For Hazardous and Wet Locations

Compact Fluorescent listed for simultaneous exposure to combustible dusts and flammable gases or vapors.

Item	Description	Catalog Number ③
<b>White Polyester Reflectors</b>		
 <b>Standard Dome</b>	For Globe Fixtures	
	Standard Dome 30° Angle	<b>KR2-ST</b> <b>KR2-AN</b>
 <b>30° Angle Dome</b>	For Glass Refractor Fixtures ❶	
	Standard Dome 30° Angle	<b>CMR-4ST ②</b> <b>CMR-4AN ②</b>
<b>Prismatic Glass Globes — Heat-Resistant ③</b>		
	Clear	<b>VPGL-2HR</b>
	Amber ④	<b>VPGL-2AM</b>
	Blue ④	<b>VPGL-2BL</b>
	Green ④	<b>VPGL-2GR</b>
	Red ④	<b>VPGL-2RE</b>
	Clear — 57/114 Watt ❶❷	<b>VPGL-4HR</b>
<b>Closed Prismatic Glass Refractors — All Heat-Resistant ③</b>		
	NEMA Type I	<b>LPG-R1</b>
	NEMA Type III	<b>LPG-R3</b>
	NEMA Type V	<b>LPG-R5</b>
<b>Closed Prismatic Polymeric Refractors — Not Listed for Class I, Zone 2 Areas</b>		
	NEMA Type II	<b>LPRF-2CP</b>
	NEMA Type III	<b>LPRF-3CP</b>
	NEMA Type IV	<b>LPRF-4CP</b>
	NEMA Type V	<b>LPRF-5CP</b>
<b>Guards</b>		
 <b>Globe Guard</b>	Globe Guard	<b>KGU2</b>
	 <b>Glass Refractor Guard</b>	Glass Refractor Guard
 <b>Globe Guard for 57 W Only</b>		Globe Guard — 57/114 W ❶❷

❶ Fixtures with refractors are not UL Listed when used with reflectors.

❷ Standard dome reflectors may interfere with bottom conduit entry if used with KPST and KPWB mounting hoods.

③ Silicone or Teflon ❶❷ coated globes are available. Contact your local sales representative.

④ Non hazardous rated globes for special applications.

❶❷ CSA Certification only.