



Product Number: 51836

Order Abbreviation: QTP 2X26CF/UNV DIM

General Description: 2 lamp T4 compact fluorescent 0-10V dimming ballast, powers one or two 26W, 18W or 13W CFL lamps or one 32W or one 42W CFL lamps. Universal Voltage, Programmed Rapid Start, Electronic Dimming ballast

Product Information

Abbrev. With Packaging Info.	QTP2X26CFUNVDIM CS/20 1/SKU
Ballast Height H (in)	1.3500
Ballast Length L (in)	4.9500
Ballast Width W (in)	2.9300
Family Brand Name	QUICKTRONIC HELIOS
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	1 or 2
Starting Method	Programmed Rapid Start
Wiring Method	Dual Entry, Color Coded, Wire Trap Connectors
Max Case Temperature	75C



QUICK 60+
SYSTEM WARRANTY

QUICKSENSE
.. .. .



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting: Refer to PIB (Product Information Bulletin) available on www.Sylvania.com or www.MySylvania.com
- 75C Max Case Temperature
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 50F/10C.