



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Load Centers](#) > Commercial/High-rise Residential

Load Centers, Commercial/High-rise Residential

Product #: TM30412C

Short Description: 125A 30CRT 3P4W 208Y/120V 10KIC CMB

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Three Phase
Input/Output Voltage	208Y/120V ac
Type	Standard
Interrupting Capacity Rating	22
Amperage	125A
Device Type	Main Breaker
Enclosure	Indoor Type 1 Enclosure, Combination
UL/CUL Listing	UL
Phase	3 Phase
1" Space	30
1/2" Space	14
Feed	Top
Door	Yes
GSA Compliance	Yes
GO Schedule	137
List Price	\$1324

Photo
Not Available

[View Larger](#)

Publications/Resources

[TM30412C](#)

Additional Resources for Three Phase

[Drawings-Outline and Dimensional](#)

[Buy Log :1-15](#)

- UL Listed (Panelboards No. 67)
- 60°/75°C Conductor Rating
- Suitable for use as service entrance equipment when installed in accordance with the National Electrical Code
- 22kAIC RMS symmetrical, Except Where Noted
- 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down
- For a listing of CSA Listed load centers, visit www.gееlectrical.com

