



Flexible Conduits & Fittings
T&B Catalog Number:

BVND-N022GT

UPC Number:

78620995124

Status:

Active

Description:

PMAFIX straight black connector with NPT threads and universal safety clip. Material - polyamide 6, thread size - 1/2 in., conduit size NW - 12.

Application

For cable protection systems in a wide range of applications

Characteristics

Very high impact resistance
Vibration proof connection to PMAFLEX conduits
High conduit pull-out strength
Very good chemical properties
Free from halogens and cadmium
Fits both conduit profiles - Fine (T) and coarse (G)
Easy installation, simply push the conduit in
Can be easily re-opened with a screwdriver

General

Material	Polyamide 6
Color	Black
Thread Type	NPT
Compatiable With	PMAFLEX, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW)	12
Fits to Conduit Size (metric)	16
Fits to Conduit Size (inches)	3/8
Thread Size (NPT)	1/2

Technical Information

Temperature Range-Continuous (Celsius)	-40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

Specifications

3dmodel	Available on Website
---------	----------------------

IP Ratings

IP Rating	IP66 stat. / IP54 dyn.
-----------	------------------------

Packaging

T&B Inner Pack	100
Package in Units	600
T&B Sold in UOM	Each
T&B Weight Per UOM	0.02 lbs. Each

Application Support

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website
PMAFIX Connectors-Safety and Sealing Systems	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com