

ABS & PVC Cement PC 6170

- Virgin PVC Resin
- Clear or Gray
- Reduced Emission VOC
- Pint or Quart

Low VOC (Volatile Organic Compound) ABS & PVC Cement conform to South Coast Air Quality Management District regulations (Rule 1168), and are used for electrical conduits and non pressure applications. All conduit schedules & classes through 6". Joins ABS to PVC, ABS to ABS, PVC to PVC.



CAT NO	UPC	CONTENTS	COLOR	STD	MSTR	WT/STD	UNIT
PV16CL	30950	Pint	Clear	12	12	14.64#	Ea
PV16GR	30955	Pint	Gray	12	12	14.64#	Ea
PV32CL	30960	Quart	Clear	12	12	26.88#	Ea
PV32GR	30965	Quart	Gray	12	12	26.88#	Ea

ABS & PVC Primer PC 6170

- Thin Solvent
- Purple
- Fast Acting
- Pint

ABS & PVC Primer is a water thin solvent to be used in conjunction with PVC cement to produce the best PVC joint possible. It also acts as a cleaner as well as a pre-softener, and is suitable for use on all types, classes, and schedules of PVC pipes and fittings.



CAT NO	UPC	CONTENTS	COLOR	STD	MSTR	WT/STD	UNIT
PR16	30975	Pint	Purple	12	12	13.56#	Ea

Roof Mastic PC 6210

- UL Classified
- Asbestos Free
- ASTM 4586, ASTM D2822
- Meets Federal Specs SS-C-153

Premium grade roof mastic can be used in wet or dry locations to patch cracks & breaks, repair seams & joints and for sealing flashings. It adheres to all surfaces, wet or dry and forms a tight, strong weathertight seal which stays soft and pliable. Applied with a trowel or putty knife, it will cure to be a durable, resilient coating of excellent adhesion and unsurpassed weathering.



CAT NO	UPC	CONTENTS	STD	MSTR	WT/STD	UNIT
RKM1	30605	1 Quart	12	12	30.60#	Ea
RKM4	30610	1 Gallon	4	4	38.52#	Ea
RKM20	30615	5 Gallon	1	1	43.94#	Ea
RKM10	10920	10 oz.	12	12	9.48#	Ea

Dark Cutting Oil PC 6220

- Petroleum Mineral Oil
- Chlorinated Additive

Dark Cutting Oil is specifically designed for threading steel and cast iron, and is recommended for cutting ferrous materials and ferrous alloys. It has been fortified with a chlorinated additive which works as an extreme pressure agent to allow an increased tolerance of alloyed or hard-grained pipe. Caution: Dark cutting oil contains active sulphur which will stain non-ferrous materials including copper, brass, stainless.



CAT NO	UPC	CONTENTS	STD	MSTR	WT/STD	UNIT
CO1	27525	1 Quart	12	12	24.96#	Ea
CO4	27530	1 Gallon	4	4	32.04#	Ea

CHEMICALS & TAPE > ABS & PVC CEMENT / PRIMER > ROOF MASTIC > DARK CUTTING OIL