



X Series
Class I, Div. 1 & 2, Groups C,D
Class II, Div. 1 & 2, Groups E,F,G
Class III

XALB Series
Class I, Div. 1 & 2, Group D
Class II, Div. 1 & 2, Groups E,F,G
Class III

Listed - File E10514
 Certified - File LR11716
See files for details or call Killark.

FEATURES-SPECIFICATIONS

**X
Features**

- Integral bushings
- Easy access covers
- Six hub styles
- Sizes 1/2", 3/4", 1"

Material/Finish

- Copper-free aluminum (less than 4/10 of 1%)
- Electrostatically applied powder coating

Ⓢ X Series 1" hub size suitable for Class I, Group D

| X DIMENSIONS | | | | | | | | |
|--------------|----------------|------------------------|----------|----------|----------|--------|--------|----------------|
| | CATALOG NUMBER | HUB SIZE | A LENGTH | B WIDTH | C HEIGHT | D | E | VOLUME CU. IN. |
| | XC-1 | 1/2" | 5-9/16" | 1-17/32" | 2-1/8" | 5/8" | — | 4.3 |
| | XC-2 | 3/4" | 5-13/16" | 1-3/4" | 2-1/4" | 11/16" | — | 6.5 |
| | XC-3 | 1"Ⓢ | 6-1/16" | 2-3/8" | 2-1/2" | 7/8" | — | 11.5 |
| | XLL-1 | 1/2" | 4-5/8" | 2-7/16" | 2-1/8" | 5/8" | 3/4" | 4.3 |
| | XLL-2 | 3/4" | 4-29/32" | 2-5/8" | 2-1/4" | 11/16" | 7/8" | 6.5 |
| | XLL-3 | 1"Ⓢ | 5-9/16" | 3-1/2" | 2-1/2" | 7/8" | 7/8" | 11.5 |
| | XLB-1 | 1/2" | 4-5/8" | 1-17/32" | 2-15/16" | 5/8" | 3/4" | 4.3 |
| | XLB-2 | 3/4" | 4-29/32" | 1-3/4" | 3-1/8" | 11/16" | 11/16" | 6.5 |
| | XLB-3 | 1"Ⓢ | 5-17/32" | 2-3/8" | 3-5/8" | 7/8" | 7/8" | 11.5 |
| | XLR-1 | 1/2" | 4-5/8" | 2-7/16" | 2-1/8" | 5/8" | 3/4" | 4.3 |
| | XLR-2 | 3/4" | 4-29/32" | 2-5/8" | 2-1/4" | 11/16" | 7/8" | 6.5 |
| | XLR-3 | 1"Ⓢ | 5-9/16" | 3-1/2" | 2-1/2" | 7/8" | 7/8" | 11.5 |
| | XT-1 | 1/2" | 5-9/16" | 2-7/16" | 2-1/8" | 5/8" | — | 4.3 |
| | XT-2 | 3/4" | 5-13/16" | 2-5/8" | 2-1/4" | 11/16" | — | 6.5 |
| | XT-3 | 1"Ⓢ | 6-11/16" | 3-1/2" | 2-1/2" | 7/8" | — | 11.5 |
| | XLRT-21 | 3/4" Ends 1/2" Side | 5-3/4" | 2-21/32" | 2-1/2" | 11/16" | — | 7 |
| | XLRT-22 | 3/4" End 3/4" Side | 5-3/4" | 2-21/32" | 2-1/2" | 11/16" | — | 7 |

**XALB
Applications**

Designed to permit straight pulls of heavy cable.

Features

- Integral bushings
- Easy access covers
- Sizes 1-1/4" thru 3"

Material/Finish

- Copper-free aluminum (less than 4/10 of 1%)
- Electrostatically applied powder coating

Ⓢ X Series 1"hub size suitable for Class 1, Group D

| XALB CONDUIT BODIES | | |
|---------------------|----------|---------------|
| CATALOG NUMBER | HUB SIZE | VOLUME CU.IN. |
| XALB-4 | 1-1/4" | 27 |
| XALB-5 | 1-1/2" | 27 |
| XALB-6 | 2" | 70 |
| XALB-7 | 2-1/2" | >100 |
| XALB-8 | 3" | >100 |

XALB Series suitable for Class 1, Group D only.

| XALB DIMENSIONS | | | |
|-----------------|-----------------|------------------|---------------|
| CONDUIT SIZE | A OVERALL DEPTH | B LENGTH OF BODY | WIDTH OF BODY |
| 1-1/4" | 4-1/16"(103) | 7-3/4"(197) | 3-15/16"(100) |
| 1-1/2" | 4-1/16"(103) | 7-3/4"(197) | 3-15/16"(100) |
| 2" | 5-7/8"(149) | 11-1/8"(282) | 4-3/4"(121) |
| 2-1/2" | 8-1/4"(209) | 17-1/2"(444) | 6-7/16"(163) |
| 3" | 8-1/4"(209) | 17-1/2"(444) | 6-7/16"(163) |

