



# T&B<sup>®</sup>

## Type A-Non-Metallic Liquidtight Conduit & Fittings T&B Catalog Number:

**UPC Number:** 3731-TB  
78621003731  
**Status:** Active  
**Description:**

1/2 in. 45 degree steel Type A liquidtight connector with insulated throat and steel retainer.

### Features

- Steel or malleable iron construction with nylon-insulated throat
- Santoprene sealing gasket includes Type 316 stainless steel retaining ring.
- NPT hub threads seal in female threads.
- Offers high mechanical pull-out strength.
- Supplied with sealing ring and steel locknut.
- Available in straight, 45 degree and 90 degree in hub sizes from 3/8 in. to 2 in..

### Application

Provides a positive seal against water, oil and dust.

### General

Trade Size (inches) 1/2  
Material Steel

### Dimension Information

Dimension A (inches) 1 3/8  
Dimension B (inches) 2 9/16

### Specifications

3dmodel Available on Website

### Packaging

T&B Inner Pack 25  
Package in Units 50  
T&B Sold in UOM Each  
T&B Weight Per UOM 40.3 lbs. per 100

### Application Support

Product Brochure-Type A Liquidtight Con- Available on Website  
nectors & Conduit  
Product Overview-Type A Liquidtight Flex-Available on Website  
ible Metal Conduit & Connectors  
T&B Sales Drawings wsd-000107  
Guide to Nonmetallic Conduit Applications Available on Website

### Notes

Santoprene is a registered trademark of Advanced Elastomer Systems.

### Certifications

RoHS Compliance Yes

## Certifications



File Nbr:  
E 23018

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)