



Type A-Non-Metallic Liquidtight Conduit & Fittings
T&B Catalog Number:

3733-TB

UPC Number:

78621003733

Status:

Active

Description:

1 in. 45 degree steel Type A liquidtight connector with insulated throat and steel retainer.

Features

Steel or malleable iron construction with nylon-insulated throat

Santoprene sealing gasket includes Type 316 stainless steel retaining ring.

NPT hub threads seal in female threads.

Offers high mechanical pull-out strength.

Supplied with sealing ring and steel locknut.

Available in straight, 45 degree and 90 degree in hub sizes from 3/8 in. to 2 in..

Application

Provides a positive seal against water, oil and dust.

General

Trade Size (inches)

1

Material

Malleable Iron

Dimension Information

Dimension A (inches)

1 7/8

Dimension B (inches)

3 1/2

Specifications

3dmodel

Available on Website

Packaging

T&B Inner Pack

5

Package in Units

25

T&B Sold in UOM

Each

T&B Weight Per UOM

67 lbs. per 100

Application Support

Product Brochure-Type A Liquidtight Connectors & Conduit Available on Website

Product Overview-Type A Liquidtight Flexible Metal Conduit & Connectors Available on Website

T&B Sales Drawings

wsd-000107

Guide to Nonmetallic Conduit Applications Available on Website

Notes

Santoprene is a registered trademark of Advanced Elastomer Systems.

Certifications

RoHS Compliance

Yes

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com