

**Type A-Non-Metallic Liquidtight Conduit**  
**T&B Catalog Number:**

TYPEA100-100

**UPC Number:**

78621097673

**Status:**

Active

**Description:**

1 in. non-metallic orange Type A liquidtight conduit.



**Features**

No metal core to fatigue from flexing or vibration  
 Smooth, seamless inner core of flexible PVC that is bonded to a coursing of flexible PVC. Between these layers is a woven nylon mesh molded for reinforcement.  
 Sunlight resistant

**Application**

Ideally suited for continuous flexing applications or vibration  
 Meets NEC, article 351, part "B" (ANSI/NFPA-70) for flexible liquidtight non-metallic conduit.

**General**

Material PVC  
 Color Orange  
 Working Temperatures -20 C to 60 C

**Dimension Information**

Size (inches) 1

**Packaging**

T&B Order Multiple 100  
 Package in Units 100  
 T&B Sold in UOM Feet  
 T&B Weight Per UOM 50 lbs. per 100

**Application Support**

Product Brochure-Type A Liquidtight Con- Available on Website  
 nectors & Conduit  
 Product Overview-Type A Liquidtight Flex-Available on Website  
 ible Metal Conduit & Connectors  
 T&B Sales Drawings wsd-000172  
 Guide to Nonmetallic Conduit Applications Available on Website

**Certifications**

RoHS Compliance Yes

**Certifications**



File Nbr:  
 E 95745

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321

