

Product Selection

Barrel Dia.	Barrel Type	Nominal Sensing Distance [mm (in.)]	Shielded	Output Configuration	Switching Frequency [Hz]	Cat. No.			
						Cable Style	Pico QD Style	Pico with Lead Style	
3	Smooth	0.6 (0.02)	Y	N.O.	5000	871C-DM1NN3-E2	—	871C-DM1NN3-AP3	
						871C-DM1NP3-E2	—	871C-DM1NP3-AP3	
		1 (0.04)			3000	871C-MM1NN3-E2	—	871C-MM1NN3-AP3	
						871C-MM1NP3-E2	—	871C-MM1NP3-AP3	
4	Threaded	0.8 (0.03)			5000	NPN	871C-D1NN4-E2	—	871C-D1NN4-AP3
						PNP	871C-D1NP4-E2	—	871C-D1NP4-AP3
		1 (0.04)			3000	NPN	871C-M1NN4-E2	—	871C-M1NN4-AP3
						PNP	871C-M1NP4-E2	—	871C-M1NP4-AP3
	Smooth	0.8 (0.03)	5000	NPN	871C-DM1NN4-E2	871C-DM1NN4-P3	—		
				PNP	871C-DM1NP4-E2	871C-DM1NP4-P3	871C-DM1NP4-AP3		
		1.5 (0.06)		3000	NPN	871C-MM2NN4-E2	871C-MM2NN4-P3	—	
					PNP	871C-MM2NP4-E2	871C-MM2NP4-P3	—	
5	Threaded	1 (0.04)		5000	NPN	871C-D1NN5-E2	871C-D1NN5-P3	—	
					PNP	871C-D1NP5-E2	871C-D1NP5-P3	—	
		1.5 (0.06)		3000	NPN	871C-M2NN5-E2	871C-M2NN5-P3	—	
					PNP	871C-M2NP5-E2	871C-M2NP5-P3	—	
Recommended cordset						889P-F3AB-2			

QD Cordsets and Accessories

Description	Page Number
Other Cordsets Available	8-2
Terminal Chambers	8-2
Mounting Brackets	2-210...2-214
End Caps	2-220
Mounting Nuts	2-221...2-222