

598-1PB22__

598-2PB22__

Dimensions are not intended to be used for manufacturing purposes.



Enclosure	Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.
Gray Enclosure	598-1PB22G	1	598-2PB22G	1
Yellow Enclosure	598-1PB22Y	1	598-2PB22Y	1
Outside Dimensions (Height x Width x Depth)	110 mm x 80 mm x 85 mm (4.33 in. x 3.15 in. x 3.35 in.)		130 mm x 80 mm x 85 mm (5.12 in. x 3.15 in. x 3.35 in.)	
Base Depth	50 mm (1.97 in.)		50 mm (1.97 in.)	
Cover Depth	35 mm (1.38 in.)		35 mm (1.38 in.)	
Cover Screw Material	Glass-Reinforced Nylon		Glass-Reinforced Nylon	
Recommended Tightening Torque	1.0...1.2 N•m (9...11 lb-in.)		1.0...1.2 N•m (9...11 lb-in.)	
Approx. Shipping Weight	232 g (0.51 lb)		271 g (0.60 lb)	

598-3PB22__

598-4PB22__

Dimensions are not intended to be used for manufacturing purposes.



Enclosure	Cat. No.	Pcs./Pkg.	Cat. No.	Pcs./Pkg.
Gray Enclosure	598-3PB22G	1	598-4PB22G	1
Yellow Enclosure	598-3PB22Y	1	598-4PB22Y	1
Outside Dimensions (Height x Width x Depth)	180 mm x 80 mm x 85 mm (7.09 in. x 3.15 in. x 3.35 in.)		250 mm x 80 mm x 85 mm (9.84 in. x 3.15 in. x 3.35 in.)	
Base Depth	50 mm (1.97 in.)		50 mm (1.97 in.)	
Cover Depth	35 mm (1.38 in.)		35 mm (1.38 in.)	
Cover Screw Material	Glass-Reinforced Nylon		Glass-Reinforced Nylon	
Recommended Tightening Torque	1.0...1.2 N•m (9...11 lb-in.)		1.0...1.2 N•m (9...11 lb-in.)	
Approx. Shipping Weight	357 g (0.79 lb)		435 g (0.96 lb)	

Note: Holes are pre-molded to fit 22.5 mm push buttons such as 800F.