

Catalog Number: LT9400-SC
Product ID: 7TAA115120R0027
UPC Number: 78599108578
Status: Active

Liquidtight Conduit Fitting, 90 Degree Bend, Trade Size 4 Inch, Malleable Iron

- Typical applications include motor and control, heating and air conditioning, outdoor lighting and transformer connection
- To positively bond conduits to a box or an enclosure indoors and outdoors
- To protect conductors from mechanical damage due to vibration and movement, and seal out cutting oils, coolants, etc.

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Steel City
Type	Connectors-90 Degree
Special Features	Screw in Ferrule and Split Sealing Ring Makes for a Quick Install While Still Providing a Liquidtight Seal that Meets UL Standards
Application	Typical Applications Include Motor and Control, Heating and Air Conditioning, Outdoor Lighting and Transformer Connection
Standard	UL E23018
Size	4 Inch
Connection	90 Degree
Material	Malleable Iron
Color	Metallic

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	4 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Material housing	Other
Surface protection	Untreated
Thread length	30.0mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	24x8.8x6.2
Weight Uom	23.23 lbs. Each

Documents / Support Tools

Technical Data Sheet Global	WSD-001295
-----------------------------	------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com