



Liquidtight Flexible Cord & Cable Fittings
T&B Catalog Number:

UPC Number: 2940AL
Status: 78621079719
Description: Active

Liquidtight Strain Relief Connector, 1 Inch, Straight, Cord Range 0.310 to 0.560 Inch, Throat Diameter 9/16 Inch, Aluminum Body, Glandnut, and Grip, Rubber Bushing

Features

- Extended range with superior strain relief.
- Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.

Application

- Provide a means for passing a cord cable into an enclosure through a bulkhead
- Suitable for Ordinary, Wet or Dry locations.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

General

Material Aluminum
Cord and Cable Types S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Dimension Information

Hub Size (inches) 1
Dimension A (inches) 1 5/16
Dimension B (inches) 1 3/4
Dimension C (inches) 1 1/16
Cord Range (inches) .310-.560
Throat Diameter (inches) 11/16

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 10
Package in Units 100
T&B Sold in UOM Each
T&B Weight Per UOM 15.5 lbs. per 100

Application Support

T&B Sales Drawings wsd-000077
Product Overview Available on Website
Specifications Available on Website
Portable Cord Selection Table Available on Website

Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com